

TEMPOMATIC MIX 2 :**SPECIFICATIONS**

Electronic basin mixer with power supply 230-12V with transformer (separate electronic control box IP65). Regulated flow rate 8l./min. with scale proof aerator and anti-blocking in flow safety device. Programmed Periodic Rinsing during 45 sec. every 24h after the last use, to prevent risks of legionella infection. Side temperature selector, reinforced fixing by 2 stainless steel rods and lock-nuts. Brand DELABIE type TEMPOMATIC MIX 2 Power supply 230-12V with transformer. Ref. 494000

x Réf. : 494000 : standard

» Programmed Periodic Rinsing during 45 sec. every 24h after the last use, to prevent risks of legionella infection.

**FONCTIONING AND APPLICATION**

- Automatic opening/closing by presenting/removing hands from sensor detection range.
- Programmed Periodic Rinsing during 45 sec. every 24h after the last use, to prevent risks of legionella infection.
- Use: all public and commercial places, medical sector and food industry, disabled person sanitariums, offices, restaurants...

PRODUCT ADVANTAGES

- **AESTHETIC:** fluid, timeless and high-tech.
- **VANDAL-PROOF:** reinforced fixing and shock-proof detection cell.
- **FULL HYGIENE** without manual contact, avoiding the propagation of bacteria/germs carried by the hands.
- **WATER SAVING:** about 80% in comparison to classical taps (due to shorter flow rate and flow duration).
- **ANTI-BLOCKING SAFETY:** avoids risk of continuous flow (automatic closing after 60 sec. of continuous detection in case of malevolence, automatic reset).
- **ANTI-SCALDING SECURITY.**
- **EASY MAINTENANCE:** independent separately accessible units and auto-diagnostic leds.
- **RELIABILITY:** corrosion-proof solenoid valve. Foolproof detection of presence.
- **SCALE PROOF AERATOR:** 5 times slower scale deposit than a standard aerator.
- **3 YEARS WARRANTY.**

